




FIRESTOP PRODUCT OVERVIEW FOR ELECTRICAL CONTRACTOR'S



IA (Intumescent Acrylic) MAX 4" EMT IN CONCRETE OR GYPSUM WALL. MAX 2" EMT IN CONCRETE OR GYPSUM.
NOTE: WALLS ALWAYS DO BOTH SIDES OF THE WALL FOR PROPER APPLICATION. USE UL TESTED SYSTEMS.
METALLIC CAJ 1302 CONC., WL 1158 GYP. NON-METALLIC CAJ 2184 CONC., WL 2129 GYPSUM.



FYRE SIL - PRODUCT USE SELFLEVELING ON FLOORS AND GUN GRADE FOR WALLS.
NOTE: WHERE A WATER TIGHT SEAL IS NEEDED. UL SYSTEM CAJ 3036 CONC. FLOOR OR BLOCK WALL



FYRE SIL – PRODUCT: BEST PRODUCT IN INDUSTRY FOR BUSWAY.
UL TESTED SYSTEM FOR CONCRETE FLOOR FB 8002



TREMSTOP CAST IN PLACE [PASS THRU](#): FOR POUR IN PLACE CONCRETE ELECTRICAL MAX 4" EMT



OUTLET BOX INSERTS OR PUTTY PADS FOR GYPSUM WALLS WHERE BOXES ARE LESS THAN 24" APART



PILLOWS FOR CABLE TRAY APPLICATIONS PS1 2" X 4" X 13.5" OR THE LARGER PS2 8" X 1.5" X 13.5"



QUICKCOMM SLEEVE 3.5" X 10.5" OR QUICKCOM KITS AVAILABLE IN 24" X 12", 34" X 18" CALL FOR PRICING
USED IN RATED FLOORS AND WALLS FOR CABLES, FIBER OPTIC OR BLANK OPENING FOR FUTURE USE.

**ALL SUBMITTALS & ON SITE TRAINING DONE BY TREMCO REPRESENTATIVE
MELINDA ALEXANDER TREMCO INC. 770-318-6378 TREMCOFIRESTOP@CS.COM**